



*Application Instructions for*

**Colour Print Classic**

**Use on Thermal and Solvent printers**

Recommended Fabrics:

- 100% Cotton
- 100% Polyester
- Poly/cotton blends
- Cotton Caps

Accessories Required: Release paper, Application Paper or Colour Print Mask.

**Material Preparation**

Classic Colour Print is specifically formulated for thermoresin, ink jet solvent and eco solvent based inks – printing and cutting systems. The two enemies of this process are dirt particles and oil from fingerprints. They will create “dropouts” or white voids in the design. **Be certain the material is clean and static free prior to printing.** Clean the surface of this material with isopropyl alcohol and allow to dry prior to printing. Use a lint free cloth to ensure that no additional dirt, dust or static is created when wiping material. Always handle material by the edges or only in areas that are not to be printed. If you experience white streaks, gaps or any other printing problems, refer to the trouble-shooting guide for the printer.

**COLOUR PROFILE: Versacamm owners please use 'TTRH - GARMENT HEAT TRANSFERS'.**

**TIPS: Let print dry for at least 12 hours before rolling, overlaying or heat applying to garments.**

**Detail Limitations**

This material was designed for contour cutting of images and limited cutting detail. When using the Classic Colour Print system, detailed parts of your design should be printed, not cut.

1. Leave material in a room temperature of 20°C or higher.
2. Feed material into your machine so that the material faces up and the carrier is on the bottom.
3. Print the image. Contour cut the image. We recommend you allow the material to dry for at least 12 hours before heat transferring the design.
4. Weed away the excess material leaving only the printed Classic Colour Print image.
5. Pre heat the garment for tens seconds in order to remove any moisture or wrinkles.
6. If your design is particularly small use Application paper or Colour Print Mask to transfer design from backing sheet.
7. Position the design on the garment, with the Application paper or Colour Print Mask on the top.
8. If you are not using application paper or Colour Print Mask cover the design with a piece of release paper in order to protect the material from the platen
9. Heat Apply –  
Temperature: 150°C  
Time: 10-15 seconds  
Pressure: Light/Medium
10. If using application paper or Colour Print Mask, wait until completely cold before peeling. If not using application paper cover with release paper and peel immediately.

**Washing Instructions:** Machine-wash inside out at 40°C using a mild detergent. Do not bleach. Iron in reverse – do not iron on to Classic Colour Print

*All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance under conditions not under manufacturer's control. Before using, please determine suitability of product for its intended use. ie, do your own wash test.*

*Warranty of product is to replace product only and not the item this has been applied to.*

*Using transfer paper may invalidate printer warranty please check with printer manufacturer or supplier.*