



*Application Instructions for*  
***Diamond***  
CLC Transfer paper for  
Light garments

Recommended Fabrics:

- 100% Cotton
- 100% Polyester
- Poly/cotton blends

*Accessories Required: Teflon sheet, Release paper*

**Important Points:**

- Please keep clean – avoid any fingerprints on printed surface.
- Print on matt side (not on printed carrier)
- Suitable for Colour Laser Printers/Copiers Not for inkjets.
- Only for White and LIGHT Garments

**Please use this as a guide only as there are too many machines to be specific.**

1. Set colour laser printers/copiers to Standard. If print fades at the end, then use thickstock mode.
2. Print **Mirror** Image.
3. Trim Excess unprinted paper away from main image.
4. **Pre Heat the bottom platen** in order to aid HOT peel.
5. Pre press the garment for 10 seconds to remove any moisture or wrinkles.
6. Apply the image face down in the required position.
7. Cover with Release paper to protect the platen from heavily dyed fabrics leaching colour.
8. Heat apply –  
Temperature: 180°C– 200°C  
Time: 10 – 15 secs  
Pressure: Medium/Strong
9. Wait 3 – 5 seconds and Peel HOT.

**Garment care & Washing:**

Turn the garment inside out, machine wash using a colour detergent. Iron in reverse – do not iron directly on to printed image. Wash at upto 40C.

**Do not use bleach, liquid detergent, and do not dry clean**

*All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance under conditions not under manufacturer's control. Before using, please determine suitability of product for its intended use. ie, do your own wash test. Warranty of product is to replace product only and not the item the transfer has been applied to.  
Using transfer paper may invalidate printer warranty please check with printer manufacturer or supplier.*